

 INDUSTRIAL FLOW SOLUTIONS™	TECHNICAL DATA			BJM Pumps® KZN-HYD6R		
	Dwg:	DS-C68-018	Rev:	1	Date:	9/3/2025

GENERAL DATA

MAX. FLOW:	1148 GPM (4345.6 L/min)
MAX. HEAD:	104' (31.6m)
MAX. SUBMERSION DEPTH:	65' (20m) or limited to length of hydraulic hose, Consult factory for deeper depths
PUMP TYPE	HYDRAULIC DRIVE SLURRY HANDLING TOP DISCHARGE
PUMP DOWN WATER LEVEL:	15" (406 mm)
SOLID SIZE:	1.38" (34.9 mm)
STRAINER OPENING:	1.38" (34.9 mm)
IMPELLER DIAMETER:	11.7" (297 mm)
DISCHARGE SIZE	6" NPT-MALE
HEIGHT	39" (991 mm)
DIAMETER (AT WIDEST POINT)	21.25" (540 mm)
SHIPPING WEIGHT:	494 lbs (224 kg)

CONSTRUCTION / MATERIAL DATA

DUAL MECHANICAL SEAL	SILICON CARBIDE/ SILICONE CARBIDE, FKM
MOTOR HOUSING	CAST IRON
PUMP VOLUTE	COATED DUCTILE IRON (1180 DPH)
WEAR PLATE	HI-CHROME
AGITATOR	HI-CHROME
IMPELLER	HI-CHROME
STRAINER/STAND	STEEL
LIP SEAL & O-RINGS	BUNA-N
ROTOR SHAFT	410 SS
EXTERNAL HARDWARE	304 SS
BALL BEARING: PERM. LUBE. UPPER	6306
BALL BEARING: PERM. LUBE. LOWER	6310

HYDRAULIC DATA

HOSE PORTS	1" NPT-FEMALE
HYDRAULIC OIL	AW 46 HYDRAULIC OIL
INPUT FLOW ¹	MAX. 25 GPM (94.6 LPM)
OPERATING PRESSURE ¹	MAX. 2150 PSI (148.2 BAR)
POWER SOURCE	ANY OPEN CENTER HYDRAULIC SYSTEM

¹ - Variable speed hydraulic motor drive

©2025 Industrial Flow Solutions Operating, LLC. All rights reserved.

Industrial Flow Solutions Operating, LLC • 104 John W Murphy Drive, New Haven, CT 06513, USA
(860) 631-3618 • www.flowsolutions.com

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



INDUSTRIAL
FLOW
SOLUTIONS™

Performance Curve

BJM Pumps® KZN-HYD6R

Dwg:


DS-C68-012

Rev:

1

Date:

9/2/2025



Curves are based on pumping water at 60 deg. F.

KZN-HYD6R - DUAL UNITS

Impeller 297 mm

Specifications subject to change without notice