

MYERS® SRM-BP

The Myers SRM-BP BasinPro Packaged Sewage System is an ideal choice for new construction or retrofit. Installer-friendly features include a 360° Top Grip for easy installation. The E-Z Switch Rod lets you easily remove the float switch without affecting the basin lid, pump or plumbing. Available with a 4/10 HP high endurance motor, with 2" solids-handling capacity. Passive radon protection provided by gas-tight seal between structural foam lid and basin.



pump only



APPLICATIONS

Sewage, high-capacity sump, effluent

SPECIFICATIONS

Capacities – 95 GPM (360 LPM)
Shut-off Head – 19' (5.8 m)
Solids Handling – 2" (50.8 mm)
Liquids Handling – Septic effluent and sewage
Intermittent Liquid Temperature – Up to 140°F (60°C)
Motor/Electrical Data – 4/10 HP, PSC, 115V, 12A, 1Ø, 60Hz
Acceptable pH Range – 5-9
Discharge, NPT – 2" (50.8 mm)
Housing – Heavy cast iron
Power Cord – 20', 16/3, SJTW
Impeller – Recessed, thermoplastic
Volute Case – Cast iron
Shaft Seal – Type 11A, carbon and ceramic
Basin Size – 24" x 24" structural foam construction

FEATURES

Fully Assembled

Pump is pre-installed in basin, with integral torque stops to ensure stability

Oil-filled Motor

For maximum heat dissipation and continuous bearing lubrication

Recessed Vortex Impeller

For free flow of liquids, solids up to 2" diameter

Anti-floatation Features

Include concrete splash lip and unique basin shape to keep the system from floating or becoming "un-installed"

Integral 360° Top Grip

For easy lifting and handling in tight spaces

Stackable Design

Allows for compact inventory.

E-Z Switch Rod

Allows removal of float switch without disassembling basin lid, or handling pump or plumbing. Additional clip for secondary float included; float sold separately.

Available With Alarm, Optional


ORDERING INFORMATION

Catalog Number	HP	Volts	Phase/Cycles	Amps	Discharge Size	Switch Type	Cord Length	Approx. Wt. Lbs.
SRM-BP	4/10	115	1/60	12	2"	Tethered Automatic	20'	50
SRM-BP-SA1*	4/10	115	1/60	12	2"	Tethered Automatic	20'	60


*Includes SA-1 alarm.

MYERS® SRM-BP


DIMENSIONS



SECTIONAL VIEW



PUMP PERFORMANCE



USA
293 WRIGHT STREET, DELAVAN, WI 53115 WWW.FEMYERS.COM
PH: 888-987-8677 ORDERS FAX: 800-426-9446

CANADA
490 PINEBUSH ROAD, UNIT 4, CAMBRIDGE, ONTARIO N1T 0A5
PH: 800-363-7867 ORDERS FAX: 888-606-5484

Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.