

BALDOR® • ***RELIANCE***

Product Information Packet

FDL3737TM

10HP,1730RPM,1PH,60HZ,215T,3752LC,TEFC,F

Part Detail							
Revision:	K	Status:	PRD/A	Change #:		Proprietary:	No
Type:	AC	Prod. Type:	3752LC	Elec. Spec:	37WGT913	CD Diagram:	CD1336A02
Enclosure:	TEFC	Mfg Plant:		Mech. Spec:	37N370	Layout:	37LYN370
Frame:	215T	Mounting:	F1	Poles:	04	Created Date:	12-10-2013
Base:	RG	Rotation:	R	Insulation:	F	Eff. Date:	09-07-2016
Leads:	2#10 A PH,3#14 B PH					Replaced By:	
Literature:		Elec. Diagram:					

Nameplate NP1280L										
CAT.NO.	FDL3737TM									
SPEC.	37N370T913G1									
HP	10									
VOLTS	230									
AMP	39									
RPM	1730									
FRAME	215T			HZ	60		PH	1		
SER.F.	1.00		CODE	H		DES	L		CL	F
NEMA-NOM-EFF	86.5		PF	96						
RATING	40C AMB-CONT									
CC						USABLE AT 208V				
DE	6307			ODE	6206					
ENCL	TEFC		SN							

Parts List		
Part Number	Description	Quantity
SA274239	SA 37N370T913G1	1.000 EA
RA260826	RA 37N370T913G1	1.000 EA
OC3050F09SP	CYL OIL CAP 50MFD/370V	2.000 EA
RE5029	MARS 91423 DOUBLE POLE 230-240V CONTACTO	1.000 EA
TPLED1024SP	THERMAL 1PH 1.5 MAN REF LED945 TDR #5817	1.000 EA
EC1216C06SP	ELEC CAP, 216-259 MFD, 250V, 2.06D X 4.	4.000 EA
37FN3002A01SP	EXFN, PLASTIC, 9.00 OD, 1.155 ID	1.000 EA
HW3200A01	3/8-16X3/4 I-BLT WELDED F/S	1.000 EA
37CB3804A35	37 CPBX W/ 1.38 DIA, MAN THERM, & RELAY	1.000 EA
37GS3015	GASKET, CAPAC BOX	1.000 EA
51XW2520A12	.25-20 X .75, TAPTITE II, HEX WSHR SLTD	4.000 EA
37CB4509	CAPAC BOX LID, STAMPED	1.000 EA
37GS3016	GASKET, CAPAC BOX LID	1.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	6.000 EA
HA6003A47	CAPAC CLAMP	1.000 EA
HA6003A45	CAPAC CLAMP - CLIP (WHITE ZINC PLATED)	2.000 EA
51XB1016A07	10-16 X 7/16 HXWSSLD SERTYB	4.000 EA
HA2001A09	SPACER, .218 ID X .937 LG	2.000 EA
RM1015	BOOT FOR MANUAL THERMALS	1.000 EA
51XN1032A28	10-32 X 1 3/4 HX WS SL SR	2.000 EA
XY1032A02	10-32 HEX NUT DIRECTIONAL SERRATION	2.000 EA
51XF2520A08	SCREW, HEX SER SLT HD, ZN 1/4-20 X .50 L	2.000 EA
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 EA
HW3001B01	BRASS CUP WASHER, FOR #8 SCREW	1.000 EA

Parts List (continued)		
Part Number	Description	Quantity
37EP3101A04	FR ENDPLATE, MACH	1.000 EA
13XF0832A08	8-32 X.50 PAN HD,SLTD, TYPE F SCREW, ZIN	6.000 EA
NS2539	INSULATOR FOR 37 FRAMESWITCH (MH1011A10)	1.000 EA
HW5100A06	W2420-025 WVY WSHR (WB)	1.000 EA
37PE3100B33	PUEP ASSEMBLY - ROUTING PUPROSES	1.000 EA
HW4600B51	SEAL 1.375 X 2.125 X 0.313 SINGLE LIP DB	1.000 EA
XY3118A12	5/16-18 HEX NUT DIRECTIONAL SERRATION	4.000 EA
36FN3004A02	EXFN XP PULLEY, ALUM, 7.38 OD, 1.379 ID	1.000 EA
80XN2520A06	1/4-20 X 3/8 SET SCREW	2.000 EA
51XB1214A20	12-14X1.25 HXWSSLD SERTYB	1.000 EA
07FH4007A52	IEC FAN CVR W/NOTCH FOR 37CB3804 CAPAC B	1.000 EA
51XW1032A06	10-32 X .38, TAPTITE II, HEX WSHR SLTD S	3.000 EA
HA1005A02	SLINGER, OD 2.00, ID 1.14, 206 BRG,	1.000 EA
HA1005A07	SLINGER, OD 2.25, ID 1.344, 307 BRG	1.000 EA
37FH4001A06	WASHDOWN IEC FH	1.000 EA
51XW1032A06	10-32 X .38, TAPTITE II, HEX WSHR SLTD S	3.000 EA
HW2501F21	KEY, 5/16 SQ X 2.375	1.000 EA
HA7000A02	KEY RETAINER RING, 1 1/8 DIA, 1 3/8 DIA	1.000 EA
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 EA
LB1115N	LABEL,LIFTING DEVICE (ON ROLLS)	1.000 EA
LB1087	LABEL,MANUAL RESET (ROLL LABEL)	1.000 EA
MJ5001A27	32220KN GRAY SEALER *MIN BUY 4 QTS=1GAL	0.001 QT
MJ1000A02	GREASE, POLYREX EM EXXON (USe 4824-15A)	0.050 LB
MG1025C02	WILKOFASG SG, 787.105, TAN	0.028 GA

Product Information Packet: FDL3737TM - 10HP,1730RPM,1PH,60HZ,215T,3752LC,TEFC,F

HA3104A25T	THRUBOLT .31-18 X 14.75 W/SHRINK TUBING	4.000 EA
TP5059	GENERIC THERMAL KIT	1.000 EA
SP5172A65	37 TYPE L TORQ STAT SWITCH CD1336A02 F1	1.000 EA
LD5000A24	LEAD ASSY, ML1400DF10 W/#10 RING 12"	1.000 EA
LC0002	CONNECTION LABEL	1.000 EA
LB1119N	WARNING LABEL	1.000 EA
MN416A01	TAG-INSTAL-MAINT no wire (1000/bx) 11/14	1.000 EA
NP1280L	ALUM FARM DUTY UL CSA CC THERMAL	1.000 EA
37PA1039	PALLET PACK GRP, PRINT PK1026A06	1.000 EA

AC Induction Motor Performance Data

Record # 21642 - Typical performance - not guaranteed values

Winding: 37WGT913-R001	Type: 3752LC	Enclosure: TEFC
-------------------------------	---------------------	------------------------

Nameplate Data				230 V, 60 Hz: Single Voltage Motor	
Rated Output (HP)	10			Full Load Torque	30.2 LB-FT
Volts	230			Start Configuration	direct on line
Full Load Amps	39			Breakdown Torque	107.2 LB-FT
R.P.M.	1730			Pull-up Torque	78 LB-FT
Hz	60	Phase	1	Locked-rotor Torque	118 LB-FT
NEMA Design Code	L	KVA Code	H	Starting Current	300 A
Service Factor (S.F.)	1			No-load Current	10 A
NEMA Nom. Eff.	86.5	Power Factor	96	Line-line Res. @ 25°C	0.131 Ω A Ph 0.388 Ω B Ph
Rating - Duty	40C AMB-CONT			Temp. Rise @ Rated Load	93°C

Load Characteristics 230 V, 60 Hz, 10 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	79	91	94	96	96	96
Efficiency	73.9	84.5	86.8	86.4	84.1	81
Speed	1784	1768	1751	1732	1707	1679
Line amperes	13.6	21	29.5	39	50	62.5

Performance Graph at 230V, 60Hz, 10.0HP Typical performance - Not guaranteed values



