

MYERS® DSW SERIES

The Myers DSW series pumps feature a stainless steel housing and volute case for the ultimate in corrosion resistance and maximum service life. This versatile pump is designed for the most demanding sewage, wastewater or effluent applications, and handles solids up to 2" in diameter.

APPLICATIONS

Domestic wastewater and septic systems, pond and waterfall

SPECIFICATIONS

Capacities – 145 GPM (549 LPM)

Shut-off Head – 42' (12.8 m)

Solids Handling – 2" (50.8 mm)

Liquids Handling – Sewage, wastewater, effluent

Continuous Liquid Temperature – 130°F (54°C)

Motor/Electrical Data – 4/10 HP, 1/2 HP, 115V/1Ø; 1/2 HP, 1 HP, 230V/1Ø; 1 HP, 460V/3Ø; oil-filled, permanent split capacitor type, continuous duty

Acceptable pH Range – 5-9

Discharge, NPT – 2" w/90° elbow

Housing – Stainless steel

Power Cord – 20', SJOW, 16 AWG

Impeller – Stainless steel

Volute Case – Stainless steel

Shaft Seal – Mechanical - carbon and ceramic



FEATURES

Stainless Steel Tough

Stainless steel housing and volute case stand tough against the most extreme corrosive environments

Stronger Starts

High-torque, permanent split capacitor (PSC) motor; no relays or starting switches to wear out

Runs Cooler

Rugged, oil-filled motor for continuous bearing lubrication and maximum heat dissipation

Continuous Duty

Leak Protection

Long-life silicon carbide or carbon ceramic seal protects motor against water leakage

Extended Service

Fully lubricated bearings and shaft seal for longer service life

Smooth Operation

Impeller is designed for clog resistance and effectively handles solids up to 2" in diameter – available in thermoplastic or stainless steel construction


ORDERING INFORMATION

Catalog Number	HP	Volts	Phase/Cycles	Discharge Size	Switch Type	Cord Length	Approx. Wt. Lbs.
DSW40P1	4/10	115	1/60	2"	Tethered Automatic*	20'	21
DSW50P1	1/2	115	1/60	2"	Tethered Automatic*	20'	25
DSW50M2	1/2	230	1/60	2"	Manual	20'	25
DSW100M2	1	230	1/60	2"	Manual	20'	26
DSW100MW4	1	460	3/60	2"	Manual	20'	26

*Piggyback

MYERS® DSW SERIES

PUMP PERFORMANCE



USA
293 WRIGHT STREET, DELAVAN, WI 53115 WWW.FEMYERS.COM
PH: 888-987-8677 ORDERS FAX: 800-426-9446

CANADA
490 PINEBUSH ROAD, UNIT 4, CAMBRIDGE, ONTARIO N1T 0A5
PH: 800-363-7867 ORDERS FAX: 888-606-5484

Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.