# **AF0402 Series Pumps**


2:1 Ratio, 4-1/4" Air Motor, 4-Ball Lower End





(Model shown w/ball valve regulator)

DIMENSIONS	
A <sup>1</sup> in (mm)	45.27 (1149.76)
B in (mm)	21.99 (558.62)
C in (mm)	19.54 (496.32)



Pump Specifications	
Ratio	2:1
Stroke (double acting)	6" (15.24 cm)
Material Inlet	1-1/2″ NPT(F) 2″ NPT(M)
Material Outlet	1"NPT(F)
Air Inlet (female)	1/2" NPT(F)
Air Inlet Pressure Range psi (bar)	30 -150 (2.1 - 10.3)
Fluid Pressure Range psi (bar)	60 - 312 (4.1 - 21.5)
Max Cycles/Minute	60
Displacement/Cycle cu in (cm3)	82.1 (1345.3)
Cycles/gal (L)	2.8 (0.74)
Flow @ 60 Cycles gpm (L/min)	21.3 (80.6)
Noise Level @ 60 psi dBA	86.5
Weight* lb (kg)	68 (30.8)
Container Suitability	Remote Mounting





#### **Transfer and Supply**

#### Materials

Paint	Chemicals	Varnishes
Enamels	Lacquers	



### 4-Ball Lower End Style

- · Designed for high volume transfer of low- and mediumviscosity fluids up to 12,500 cPs.
- · Fluid delivery up to 32.8 gpm (124.0 L/min)

Pump Model**	Plunger Material	Upper Packings	Lower Packings	Lower Pump Model	Pump Service Kit			
Lower Pump Model Material - 300 Series/CF8M Stainless Steel								
AF0402M11HF48	17-4 Stainless Steel, Ceramic Coated	UHMW-PE/Leather (Staggered)	UHMW-PE	67200-F4B	637317-F4B			
AF0402M11RS48	17-4 Stainless Steel, Ceramic Coated	Glass Filled PTFE/ UHMW-PE (Staggered)	Virgin PTFE	67200-R4B	637317-R4B			
AF0402M11KS48	17-4 Stainless Steel, Ceramic Coated	Glass Filled PTFE	Virgin PTFE	67200-74B	637317-74B			
AF0402M11FF48	17-4 Stainless Steel, Ceramic Coated	UHMW-PE	UHMW-PE	67200-C4B	637317-C4B			

<sup>\*\*</sup>Add "-1" to Model No. for Ball Valve Regulator

## RECOMMENDED ACCESSORIES













Mounting Post



67442


Ball Valve

Regulator





637489 Universal Air Motor Service Kit



For manuals, flow curves, and more







