



# TECHNICAL DATA

# Dewatering Pumps S6000 HV

STANCOR

Dwg: DS-A18-072 Rev: Date: 11/16

## MOTOR SPECIFICATIONS

Motor Design	NEMA design B, squirrel cage induction, air filled
Motor Type	Enclosed submersible, IP 68
Maximum submergence	65 feet (20m)
Insulation Class	Class F, rated at 155° C
Motor Protection	Bi-metallic Thermal Switch
Bi-Metallic Temp Trip	130° C ± 5° C
Service Factor	1.15
Max. Liquid Temperature	104°F (40°C)
Voltage Tolerance	± 10% from nominal



## MOTOR DATA, 60Hz

Model	Phase	Output Power BHP	Volts	Full Load Amps	Locked Rotor Amps	NEMA Code Letter	Power Factor 100% Load	Motor Efficiency 100% Load	Pole/Speed (rpm)
S6000HV	3	60	460	77	462	M	0.85	0.89	4/1750
			575	62	372	G	0.85	0.89	4/1750
			950	37	222	G	0.85	0.89	4/1750

## MATERIALS OF CONSTRUCTION

Upper Motor Lid	356-T6 Aluminum
Motor Housing	356-T6 Aluminum
Oil Chamber	AISI 304 Stainless Steel
Volute	356-T6 Aluminum - Rubber Lined
Wear Plate	356-T6 Aluminum - Rubber Lined
External Hardware	AISI 304 Stainless Steel
O-Rings	NBR
Motor Shaft	AISI 416 Stainless Steel
Upper Bearing	Deep groove ball bearing, double sealed
Lower Bearing(s)	Two heavy duty angular contact ball bearings
Upper Shaft Seal	Carbon/Ceramic
Lower Shaft Seal	SiC/SiC
Impeller	17-4PH Stainless Steel

## DIMENSIONS, WEIGHT, AND MISC.

Pump weight (without cable)	1200 lbs (545 kg)
Discharge size	8 inch NPT male vertical (6", 10" optional)

## CABLE SPECIFICATIONS

MODEL	PHASE/VOLTAGE	POWER CABLE	LENGTH	OUTER JACKET
S6000HV	3Ø-460V	4/3 G-GC	50' Standard	CPE, Heavy Duty
	3Ø-575V	4/3 G-GC	50' Standard	CPE, Heavy Duty
	3Ø-950V	10/3 SHD-GC	50' Standard	CPE, Heavy Duty

Specifications subject to change without notice