



INDUSTRIAL
FLOW
SOLUTIONS™

TECHNICAL DATA

BJM Pumps® XP-SKX22CSS

Dwg:

DS-C40-011

Rev:

1

Date:

9/2/2025

GENERAL DATA

APPROVALS:	EXPLOSION PROOF FM APPROVED CLASS1, DIVISION 1, GROUP C & D	
MAX. FLOW:	281 GPM (1063.7 LPM)	
MAX. HEAD:	50' (15.2m)	
MAX. SUBMERSION DEPTH:	65' (20 m) or limited to length of power cord, Consult factory for deeper depths	
PUMP TYPE:	SOLIDS HANDLING, NON-CLOG SHREDDER	
MINIMUM SUBMERSION DEPTH FOR CONT. DUTY ² :	29.5" (749.3 mm)	
SOLID SIZE:	1.6" (40.6 mm)	
IMPELLER DIAMETER:	4.45" (113 mm)	
DISCHARGE SIZE:	3" NPT-MALE	
SLIDE RAIL SYSTEM	3" NON-SPARKING	
PUMP WEIGHT (without cable):	157 lbs (71 kg)	
SHIPPING WEIGHT:	168 lbs (76 kg)	

CONSTRUCTION / MATERIAL DATA

UPPER MECHANICAL SEAL	CARBON/CERAMIC, FKM
LOWER MECHANICAL SEAL	SILICON CARBIDE/ SILICONE CARBIDE, FKM
MOTOR HOUSING	CAST IRON, EPOXY COATED
PUMP VOLUTE	316 SS
SUCTION COVER	316 SS
IMPELLER	316 SS
IMPELLER SHREDDER BLADE	TUNGSTEN CARBIDE
LIP SEAL & O-RINGS	FKM
ROTOR SHAFT	403SS
EXTERNAL HARDWARE	304 SS
BEARING, PERM. LUBRICATED, UPPER:	6305ZZC3
BEARING, PERM. LUBRICATED, LOWER:	6307ZZC3

ELECTRICAL / MOTOR DATA

MOTOR: HP, TYPE, RATING	3, SUBMERSIBLE, (CONTINUOUS DUTY ²)			
MOTOR RPM	3450			
MOTOR INSULATION CLASS	F			
MOTOR SERVICE FACTOR	1.15			
VOLTAGE - 3PH - 60Hz	208V	230V	460V	575V
CURRENT F.L.A.	9.4	8.9	4.5	3.6
LOCKED ROTOR CURRENT (LRA)	62	59	29.5	24
POWER CABLE: GAGE-LENGTH	AWG 14/4, 50' (15m) SOOW			
SENSOR CABLE: ¹ GAGE-LENGTH	AWG 14/4, 50' (15m) SOOW			
MOTOR PROTECTION	TWO NORMALLY CLOSED THERMOSTATS			
SEAL LEAK DETECTOR ¹	SINGLE ELECTRODE LEAKAGE DETECTOR			
MAXIMUM LIQUID TEMPERATURE	104°F (40°C)			

1 - Requires seal fail and thermal circuit in control panel for warranty validity.

2 - Continuous duty motor - see minimum submersion depth above.

©2025 Industrial Flow Solutions Operating, LLC. All rights reserved.

Industrial Flow Solutions Operating, LLC • 104 John W Murphy Drive, New Haven, CT 06513, USA

(860) 631-3618 • www.flowsolutions.com



INDUSTRIAL
FLOW
SOLUTIONS™

PERFORMANCE CURVE

BJM Pumps® XP-SKX22CSS

Dwg:


DS-C40-005

Rev:

1

Date:

6/24/2025



Test Standard : HI 11.6 Gr 3B
Tested with water at 20°C

22CSS - Dual Units

Frequency
Pump Speed
Impeller

60 Hz
3450 RPM
113mm

Specifications subject to change without notice