



**DIMENSIONS - INCH**

**WEIGHT: lb**

MODEL	A	A1	A2	A3	B	B1	B2	D	D1	D2	D3	D4	D5	D6	DN	E	F	G	P	P1	H	H1	H2	H3	WT
SV-500	18.50	4.33	10.12	6.69	8.58	3.86	4.72	7.24	5.75	6.10	5.31	5.75	5.91	5.91	3	0.51	M12	0.55	90°	90°	24.92	18.43	6.30	9.41	123.2
SV-500	18.50	4.33	10.12	6.69	8.58	3.86	4.72	7.24	5.75	6.10	5.31	5.75	5.91	5.91	4	0.51	M12	0.55	90°	90°	24.92	18.43	6.30	9.21	123.2
SV-750	18.50	4.33	10.12	6.69	8.58	3.86	4.72	7.24	5.75	6.10	5.31	5.75	5.91	5.91	3	0.51	M12	0.55	90°	90°	26.50	20.00	6.30	9.41	136.4
SV-750	18.50	4.33	10.12	6.69	8.58	3.86	4.72	7.24	5.75	6.10	5.31	5.75	5.91	5.91	4	0.51	M12	0.55	90°	90°	26.50	20.00	6.30	9.21	136.4

C.W.L.:Continuous Running Water Level

WT: Pump Weight

L.W.L.:Lowest Running Water Level

Specifications subject to change without notice