

BALDOR® • RELIANCE

Product Information Packet

SUM72004-4

20HP,1800RPM,3PH,60HZ,210TY,TENV,FOOTLE

Part Detail							
Revision:	-	Status:	PRD/A	Change #:		Proprietary:	No
Type:	AC	Prod. Type:		Elec. Spec:	E02775-A-A009	CD Diagram:	416820-2
Enclosure:	TENV	Mfg Plant:		Mech. Spec:		Layout:	066930-502
Frame:	210TY	Mounting:	V1	Poles:	04	Created Date:	04-09-2015
Base:		Rotation:	R	Insulation:	F	Eff. Date:	04-13-2015
Leads:						Replaced By:	
Literature:		Elec. Diagram:					

Nameplate 000613007AC		
CLASS I GROUP	C D X	NO. <input type="text"/>
CLASS II GROUP	X X X	
OPERATING TEMP CODE	T3C	

Nameplate 000613007MN										
CAT NO	SUM72004-4		SPEC NO.	P21G2758						
HP	20	AMPS	52.4/26.2		VOLTS	230/ 460		DESIGN	B	
FRAME SIZE	X210TY	RPM	1740		HZ	60	AMB	40	SF	1.15
D.E. BRG.	60BC02JPP30A		PH	3	DUTY	*		INSUL	F	
O.D.E. BRG.	30BC02JPG30A		TYPE	P	ENCL	TENV		CODE	G	
			POWER FACTOR			NEMA-NOM-EFF				
			MAX CORR KVAR			GUARANTEED EFFICIENCY				
					NEMA NOM/CSA QUOTED EFF @			100% LOAD		
SER.NO.			MOTOR WEIGHT	420		LBS.				
	FINAL CONN @ 460V *15 MIN IN									
	AIR ;SUB.IN WATER/SEWAGE ONLY									
	SEE MANUAL FOR MAXDEPTH;									

Nameplate 000613007MR										
CAT NO	SUM72004-4	SPEC NO.	P21G2758							
HP	20	AMPS	52.4/26.2		VOLTS	230/ 460		DESIGN	B	
FRAME SIZE	X210TY	RPM	1740		HZ	60	AMB	40	SF	1.15
D.E. BRG.	60BC02JPP30A		PH	3	DUTY	*		INSUL	F	
O.D.E. BRG.	30BC02JPG30A		TYPE	P	ENCL	TENV		CODE	G	
SER.NO.			POWER FACTOR			NEMA-NOM-EFF				
			MAX CORR KVAR			GUARANTEED EFFICIENCY				
			NEMA NOM/CSA QUOTED EFF @			100% LOAD				
			MOTOR WEIGHT	420		LBS.				
	FINAL CONN @ 460V *15 MIN IN									
	AIR ;SUB.IN WATER/SEWAGE ONLY									
	SEE MANUAL FOR MAXDEPTH;									

Parts List		
Part Number	Description	Quantity
SA297392	SA P21G2758	1.000 EA
RA284354	RA P21G2758	1.000 EA
000613007AC	UL NAMEPLATE FOR HAZARDOUS LOCATIONS	1.000 EA
000613007MN	NP,MEDIUM AC,NO CERT,STD INDUSTRIAL	1.000 EA
000613007MR	NP, MEDIUM AC, CSA, STD INDUSTRIAL	1.000 EA
000692000EJ	NAME PLATE	1.000 EA
000901001AA	LABEL WARNING	1.000 EA
001575000B	WIRING DIAGRAM	1.000 EA
424476003WA	WIRING DIAGRAM MEDIUMA	1.000 EA
034692002AE	HCSPP 1/4" 304 S.S.	1.000 EA
004824015A	GREASE POLYREX EM	0.100 LB
032018012DG	HHCS 1/2-13X1-1/2 316S.S	4.000 EA
032130010DC	HSHCS 1/2-13X1-1/4 304SS	4.000 EA
032620020JD	HSSS 10-24X5/8L 304S.S.	1.000 EA
034692003AE	PPLG 3/8" 304 S.S.	2.000 EA
047174005C	SNAP RING	1.000 EA
047174005D	SNAP RING	1.000 EA
064262012C	SEAL	1.000 EA
064262012D	SEAL	1.000 EA
088207001AA	BRKT,DE,210SUB 88207-1WA	1.000 EA
088208001AA	MTG PLATE EX210Y SUBMERSIBLE 088208001WB	1.000 EA
413412004A	SUBM MOISTURE PROBE	2.000 EA
413412005S	LEAD WIRE ASSY(BLANKET	1.000 EA
413480001R	RESISTOR ASSEMBLY-BLANKET	1.000 EA

Parts List (continued)		
Part Number	Description	Quantity
421900144FU	ORING	1.000 EA
421900144FU	ORING	1.000 EA
603761001AA	LABYRINTH	1.000 EA
032018006BM	HHCS 5/16-18X3/4 PLTGRN.	1.000 EA
032018006BM	HHCS 5/16-18X3/4 PLTGRN.	1.000 EA
032018010CG	HHCS 3/8-16X1-1/4L 316SS	4.000 EA
032080003JB	HWHMS 10-24X3/8L PLTED	4.000 EA
032080003LB	HWHMS 1/4-20X3/8L PLTED	6.000 EA
034036013AB	LCKW 5/16 EXT.TOOTH LCKW	1.000 EA
047024003AH	T/LUG AMP 34112	4.000 EA
047024003E	TERMINAL LUG	9.000 EA
415031017A	NUT W/WASHER 10-24 C.PLT	4.000 EA
415031017B	NUT W/WASHER1/4-20 C.P	6.000 EA
421900092FU	ORING	1.000 EA
609181014D	HEAT SHRINK TUBING 3/4	10.000 EA
700385014DA	CCA #4 25' 210/250	1.000 EA
004824007K	SPECIAL PAINT	0.100 EA
033775004EA	DRSCR #6-1/4 304 S.S.	4.000 EA
034180009FD	KEY 3/8X3/8X1-1/8 303 SS	1.000 EA
088206001AB	BRKT,ODE,210SUB 88206-1WB	1.000 EA
421900144FU	ORING	1.000 EA
004824018AF	SHELL ROTELLA OIL 10W	2.500 LB
032018008BG	HHCS 5/16-18X1 BRASS-447	3.000 EA
032018012DG	HHCS 1/2-13X1-1/2 316S.S	4.000 EA

000901001AA	LABEL WARNING	1.000 EA
B3630-9	SUBM THERMOSTAT TAG	1.000 EA
B-3664002	TAG, (NON REGREASABLE)	1.000 EA

REL. S.O.	FRAME	HP	TYPE	PHASE/HERTZ	RPM	VOLTS
	210TY	20	P	3/60	1740	230/460
AMPS	DUTY	AMB °C/ INSUL.	S.F.	NEMA DESIGN	CODE LETTER	ENCL.
52.4/26.2	CONT	40/F	1.15	B	G	SUB
E/S	ROTOR	TEST S.O.	TEST DATE	STATOR RES (@25 °C OHMS (BETWEEN LINES))		
537473	418425-45YE	---	---	.172/.689		

PERFORMANCE


LOAD	HP	AMPERES	RPM	INPUT KW	POWER FACTOR	% EFFICIENCY
NO LOAD	0	10.2	1800	.878	10.8	0
1/4	5.01	12.0	1786	4.70	49.1	79.6
2/4	10.0	15.6	1772	8.68	69.7	86.1
3/4	15.0	20.5	1757	12.8	78.6	87.2
4/4	20.0	26.2	1740	17.2	82.7	86.6
5/4	25.0	32.5	1720	21.9	84.6	85.1

SPEED TORQUE

	RPM	TORQUE % FULL LOAD	TORQUE LB.-FT.	AMPERES
LOCKED ROTOR	0	193	116	141
PULL UP	540	152	92.0	131
BREAKDOWN	1517	253	153	86.8
FULL LOAD	1740	100	60.4	26.2

AMPERES SHOWN FOR 460. VOLT CONNECTION. IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE

REMARKS : CALCULATED DATA
SUBMERSIBLE MOTOR
15MIN IB AIR, CONT IN LIQUID

 <p>A MEMBER OF THE ABB GROUP</p>	DR. BY	D. M. BYRD	<p>A-C MOTOR PERFORMANCE DATA</p> <p>E02775-A-A009</p> <p>ISSUE DATE 01/25/05</p>
	CR. BY	T. S. WILLIAMS	
	APP. BY	D. M. BYRD	
	DATE	01/28/05	

